

TRILWAX™ B

Polymer Lubricant (Behenamide)

TRILWAX B is a process lubricant, slip aid and anti-block for a variety of polymers. TRILWAX B is based on fully saturated primary fatty amid.

Target Polymers: Polypropylene, Polyethylene and Rubber Compounds

Properties

Appearance	Free Flowing Beads
Color (Gard.)	4.0 Max
Amid Content	98% Min
Moisture	0.25% Max
Acid Value	1.0 Max
Shelf Life	1 Year Min

TRILWAX B is biodegradable.

TRILWAX B should be handled with normal safety precautions such as gloves & safety goggles.

TRILWAX B should be stored in a dry cool area in closed containers.

TRILWAX B is packaged in 55 lb bags.

TRILWAX B is TSCA, EINECS, DSL, registered.



The information in this data sheet is meant as a suggestive guide in formulating and evaluation of performance. Customer takes responsibility in the decision to use product in desired application. The information is given to the best of our knowledge but without obligation. We are not liable for any wrong advice or any advice we may have failed to give. This data sheet becomes invalid as soon as a new edition has been published.

Trillium Specialties LLC
10437 Innovation Drive, B21
Wauwatosa, WI 53122
T: 262-821-9175
F: 262-821-9176
www.trilliumspec.com